



## OPS72D

### OPS ON BOARD COMPUTER

Hisense interactive displays feature an integrated OPS slot, allowing a powerful on-board PC to be seamlessly embedded. Equipped with high-performance Intel® processor, the OPS delivers desktop-level performance within the display, ensuring enhanced flexibility, broad compatibility, and streamlined deployment.

### Highlights



#### 13th Gen Intel Core Processor

Powered by a 13th Gen Intel Core processor, delivering high-performance computing and efficient multitasking.



#### High Speed Storage

Fast data access and ample storage capacity (16GB+512GB) enables smooth and reliable performance for demanding applications.



#### WiFi 6 & Bluetooth 5.3 connectivity

Ultra-fast wireless connectivity with WiFi 6 and stable, low-latency device pairing via Bluetooth 5.3.



#### Multi-Interface expansion capability

Supports a wide range of interfaces for flexible connection to external devices.



#### Enhanced productivity & Security

Built on Windows 11 Pro, the OPS enhances productivity with advanced security, smooth multitasking, and remote management via Hisense VisionInfo.



#### Energy-Efficient Operation

Delivers energy-efficient performance under demanding workloads, achieving an optimal balance between power consumption and performance.



## Specifications

### OPS

<b>Model Name</b>	OPS72D
<b>CPU</b>	Intel Core™ I5-13420H
<b>RAM</b>	8GB
<b>SSD</b>	256GB
<b>LAN</b>	Integrated 10/100/1000M Adaption
<b>WIFI</b>	WIFI 6
<b>Bluetooth</b>	Bluetooth 5.3
<b>USB 3.0</b>	4
<b>USB 2.0</b>	/
<b>Type-C</b>	1
<b>HDMI out</b>	1 (2.0)
<b>DP out</b>	1 (1.4)
<b>VGA</b>	/
<b>Mic in</b>	1
<b>Line out</b>	1
<b>HDD LED</b>	1
<b>Power LED</b>	1
<b>Power Requirements</b>	12V-19V DC
<b>Max Power</b>	80.7 W
<b>Standby Power</b>	2.9 W
<b>Color</b>	Black
<b>Dimension LxWxH</b>	180 x 119 x 30 mm
<b>Net Weight</b>	0.60kg
<b>Operation Temperature</b>	-10°C - 45°C
<b>Operation Humidity</b>	10%-90%
<b>Storage Temperature</b>	-20°C - 60°C
<b>Storage Humidity</b>	10% - 90%
<b>System</b>	Win11-Pro
<b>Certification</b>	CB / CE / UKCA / FCC / IC / RCM / Rohs / UL4200A
<b>Adaptive Model</b>	65/75/86WE3FE 65/75/86WM6FE-A 65/75/86WE6GE 100WE6GE

\* Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.