



46L35B5U

46" LCD VIDEO WALL



Create a powerful visual experience with pixel perfect clarity with our latest video wall solutions. With an extra narrow bezel, Hisense video walls seamlessly recreate your desired content across almost any configuration style.

Highlights



Ultra-narrow bezel

An ultra-narrow 3.5mm bezel-to-bezel width creates a seamless and more perfect picture.



Round-the-clock operation

The Hisense L35B5U series can be used as reliable display 24 hours a day, 7 days a week.



178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees, or visitors that will view L35B5U displays from diverse angles while passing by.



500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



Anti-Glare

Optical technology diffuses mirror-like reflections and bright lights to help keep what's on your screen clear and visible.



1200:1 Ultra-high contrast

1200:1 ultra-high contrast display, providing eye-catching vivid visuals any time of the day or night, with outstanding color performance.



Specifications

Display

Panel size	46"
Brightness	500 nits
Resolution	1920 x 1080
Contrast Ratio	1200:1
Back-Light	D-LED
Color	16.7M (8bit)
Viewing Angle	178°/178°
Refresh Ratio	8 ms
Surface Treatment	Anti-glare Coating, 3H Scratch Resistant Coating, Front Polarizer, Haze 25%
Usage time	24/7
MTBF	50,000 hrs
Orientation	Landscape & Portrait

Physical

Splice Pitch	0.138 in (3.5 mm)
VESA	400 x 400 mm, M6
Set Dimension	40.2 x 22.7 x 3.8 in
Packed Dimension	45.7 x 29.5 x 9.4 in
Net Weight	45.9 lbs
Packed Weight	62.8 lbs
20GP container capacity (pcs)	135
40GP container capacity (pcs)	273

Connectivity

Interface	HDMI (2.0) x 1 (In) HDMI (1.4) x 1 (In) DP (1.2) x 2 (In & Out) DVI x 1 (In) VGA x 1 (In) RS232 x 2 (In & Out)
-----------	---

Speaker

Built-in Speaker	No
------------------	----

Power

Voltage	100-240V 50/60Hz
Power Consumption	150W

Software

OS	Yes
Language	English

Environment

Operation Temperature	50-104°
Operation Humidity	10-80% RH

Media Player compatibility

OPS Type Compatible	No
---------------------	----

Accessories

Basic	Remote Control, power cord, Ethernet cable, User Manual, RS232 connector, & infrared reception
Optional	Optional Wall Mount, Control Software, Process System

Certification

Certification	CB/CE/ERP
---------------	-----------

Display Dimensions

