



# 55L35B5U

## 55" LCD VIDEO WALL



Create a powerful visual experience with pixel perfect clarity with our latest video wall solutions. With an extra narrow bezel, Hisense video walls seamlessly recreate your desired content across almost any configuration style.

### Highlights



#### Ultra-narrow bezel

An ultra-narrow 3.5mm bezel-to-bezel width creates a seamless and more perfect picture.



#### Round-the-clock operation

The Hisense L35B5U series can be used as reliable display 24 hours a day, 7 days a week.



#### 178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees, or visitors that will view L35B5U displays from diverse angles while passing by.



#### 500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



#### Anti-Glare

Optical technology diffuses mirror-like reflections and bright lights to help keep what's on your screen clear and visible.



#### 1200:1 Ultra-high contrast

1200:1 ultra-high contrast display, providing eye-catching vivid visuals any time of the day or night, with outstanding color performance.



Specifications

Display

|                   |   |
|-------------------|---|
| Panel size        | 55"   |
| Brightness        | 500 nits  |
| Resolution        | 1920 x 1080   |
| Contrast Ratio    | 1200:1  |
| Back-Light        | D-LED   |
| Color             | 16.7M (8bit)  |
| Viewing Angle     | 178°/178°   |
| Refresh Ratio     | 8 ms  |
| Surface Treatment | Anti-glare Coating, 3H Scratch Resistant Coating, Front Polarizer, Haze 25% |
| Usage time        | 24/7  |
| MTBF              | 50,000 hrs  |
| Orientation       | Landscape & Portrait  |

Physical

|                               |                      |
|-------------------------------|----------------------|
| Splice Pitch                  | 0.138 in (3.5 mm)    |
| VESA                          | 400 x 400 mm, M6     |
| Set Dimension                 | 47.8 x 26.9 x 3.7 in |
| Packed Dimension              | 53.5 x 33.1 x 9.4 in |
| Net Weight                    | 61.9 lbs             |
| Packed Weight                 | 83.8 lbs             |
| 20GP container capacity (pcs) | 74                   |
| 40GP container capacity (pcs) | 152                  |

Connectivity

|           |   |
|-----------|---|
| Interface | HDMI (2.0) x 1 (In)<br>HDMI (1.4) x 1 (In)<br>DP (1.2) x 2 (In & Out)<br>DVI x 1 (In)<br>VGA x 1 (In)<br>RS232 x 2 (In & Out) |
|-----------|---|

Speaker

|                  |    |
|------------------|----|
| Built-in Speaker | No |
|------------------|----|

Power

|                   |                  |
|-------------------|------------------|
| Voltage           | 100-240V 50/60Hz |
| Power Consumption | 240W             |

Software

|          |         |
|----------|---------|
| OS       | Yes     |
| Language | English |

Environment

|                       |           |
|-----------------------|-----------|
| Operation Temperature | 50-104°   |
| Operation Humidity    | 10-80% RH |

Media Player compatibility

|                     |    |
|---------------------|----|
| OPS Type Compatible | No |
|---------------------|----|

Accessories

|          |  |
|----------|--|
| Basic    | Remote Control, power cord, Ethernet cable, User Manual, RS232 connector, & infrared reception |
| Optional | Optional Wall Mount, Control Software, Process System  |

Certification

|               |           |
|---------------|-----------|
| Certification | CB/CE/ERP |
|---------------|-----------|

Display Dimensions

