

65B4E31T

65" 4K UHD DIGITAL SIGNAGE DISPLAY



Hisense Digital Signage Displays are ideal for retail and business environments. The products are the perfect backbone of a digital broadcasting platform in supermarkets, restaurants, stadiums, shopping malls and office buildings. A combination of seamless design and enhanced 500 nits brightness will ensure your digital content vividly stands out from the crowd.

Highlights



Smart CMS

Hisense's CMS platform allows you to edit and arrange playlists, making content management easy and user-friendly. It supports all rich media content in synchronous playback over a multitude of commercial displays.



Landscape & Portrait

Both landscape and portrait orientations are possible, providing you with endless creative and functional possibilities to fulfill your commercial or informative goals.



178° Wide viewing angle

The wide viewing angle delivers consistent and accurate sharpness and color contrast for the best viewer experience.



4K Ultra HD

18/7 Operational Hours

The 4K Ultra HD picture quality ensures perfect color and rich details in all possible broadcasting surroundings, ranging from shops to restaurants and office buildings.

Designed with dual-core System on Chip (SoC) technology the

Hisense E series can be used for broadcasting both offline

and cloud based content 18 hours a day, 7 days a week.



500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions



Customization

Hisense displays support a variety of on-screen customizations such as custom startup logo, startup animation, wallpaper and many more. Creating a uniform look & feel for all viewers.



Automatic time zone

When connected to the Internet each display will automatically synchronize to its local time zone. Making sure scheduled media broadcast is always in sync.









Specifications

Digital Display Panel

| Backlight | DLED |
|--------------------------|----------------------|
| Size | 65" |
| Resolution | 3840 x 2160 |
| Refresh rate | 60HZ |
| Color | 1.07G (8 Bits+FRC) |
| Brightness | 500 nits (typ) |
| Contrast (typ) | 1200:1 (typ) |
| Response time (typ) | 8ms (typ) |
| Viewing angle (Min.) | 178°/178° |
| Color gamut | 72% |
| Haze | 1% |
| Orientation | Landscape & Portrait |
| Lifetime (typ) | 50,000 Hours |
| Operational (Hours/Days) | 18/7 |

Power

| Input | AC 100V-240V @ 50/60HZ |
|---------------------|------------------------|
| Power Consumption | 200W |
| Standby consumption | <0.5W (standby mode) |

Physical

| Bezel Color | Black |
|---------------------------|----------------------|
| Set Dimension (W×H×D) | 57.6 × 33.0 × 3.7 in |
| Bezel width (T/L/R/B) | T/B/L/R: 0.59 in |
| Net Weight | 60.1 lbs |
| Packing Dimension (W×H×D) | 63.6 × 39.3 × 7.4 in |
| Packed Weight | 69.2 lbs |
| VESA | 400mm x 400mm |

System

| OS | Android 8.0 |
|----------|-------------|
| DDR | 2G |
| ROM | 16G |
| Language | English |

Speaker

| Built in speaker | 8W x 2 | |
|------------------|--------|--|

Control Method

| Remote | IR | |
|--------|------------------|--|
| RS232 | 1 x RS232 (RI45) | |

Connectivity

| WIFI | Yes |
|-------------|-------------------------------|
| LAN | RJ45 × 1 |
| SD /TF Card | TF × 1 |
| USB | USB × 2/HDMI × 2/Audio in × 1 |
| Input | Audio × 1 |
| Output | Headphone Jack |

Environment

| Temperature | 0 - 104°F |
|-------------|-----------|
| Humidity | 20% - 80% |

What's in the box

| Basic | Power cord |
|-------|-------------------|
| | Remote controller |
| | RS232 cable |
| | Battery |
| | User manual |
| | HDMI Cable |

Dimensions





