Hisense



HT008E

WIRELESS SCREEN TRANSMISSION

(Compatible with WM6FE, MR6DE, MR61DE-E Series)

The HT008E wireless screen transmission dongle connects to a device's USB-C port and transmits its on-screen content to the digital whiteboard for all to see. Simply connect it to your device and press the button to instantly display the content on the whiteboard via fast and stable streaming (Windows/Mac supported).

Highlights

Crystal 4K Transmission

Enable attendees to easily see what is being shared on the screen. This clear screen-sharing feature makes it easy to set up an engaging work and study environment.

Instant Pairing

Experience instant meeting starts with a quick 3-second connection. The system will automatically recognize the HT008E for future connections.

Seamless Share, Smarter Meet

Enjoy seamless, uninterrupted screen sharing for superior meeting quality. This stable connection ensures consistently efficient collaboration.

WiFi-Free Sharing Anywhere

No HDMI, Type-C cables, apps, or even Wi-Fi required. Replace traditional screen-sharing hardware with a wireless casting dongle – enabling instant presentations anytime, anywhere.

Specifications

HT008E	
Color	Black
Connect Number	1 received device (same time)
Button	1
Port	Type-C
Working Voltage	5V
Video Resolution	3840 x 2160 @ 30 Hz
Transmission Distance	15m
Plug and Play	Support
WiFi Module	WiFi 6
Indicator Light	1. Blinking when connecting 2. White color when using
Certification	cTUVus+CB / IC / CE-RED / UKCA / CE
Package Size (W x H x D)	213 x 100 x 29 mm
Hot Plug	Support
Working Temperature	-10°C ~ +45°C
Working Humidity	≤95%
Adaptive Model	MR6DE Series, MR61DE-E Series, WM6FE Series, WM6FE-A Series, HAI0108"/136"163"
OS Supported	Windows10/11 and above, Mac 10.9 and above

*Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.