



HT002A

WIRELESS SCREEN TRANSMISSION

The HT002A wireless screen transmission dongle connects to the USB port of a device and transmits the on-screen content to the Digital Whiteboard for everyone to see. Connect it to your device and with a single button press, the content will be instantly displayed on the whiteboard through fast and stable streaming (iOS / Android / Windows / Mac supported).

Highlights



One Click Connect

Easily connect to your device with a single button press, transmitting to the on-screen content to the digital whiteboard



Fast and Stable Streaming

The HT002A Wireless Screen Transmission displays content to your whiteboard easily through fast and stable streaming without any interruptions, supporting iOS / Android / Windows and Mac

Specifications

HT002A

Color	White
Logo	Hisense
Connect Number	1 received device (same time)
Button	1
Port	USB2.0 A type
Working Voltage	5V
Video Resolution	FHD 60Hz
Transmission Distance	15m
Main IC	RK3036
Plug and Play	Support
WiFi Module	NA
Indicator Light	1. Blinking when connecting 2.White color when using
Certification	CE/CB
Hot Plug	Support
Working Temperature	-10°C ~ +45°C
Working Humidity	≤95%

HISENSE B2B EUROPE

Beechavenue 139,
1119 RB Schiphol-Rijk,
Netherlands

www.hisense-b2b.com
sales@hisense-b2b.com