



## 46L35B5U

### 46" LCD VIDEO WALL

Hisense Commercial Display solutions are perfect for high volume retail and corporate installation. A combination of seamless design and enhanced brightness ensure digital content vividly stands out from the crowd. The Hisense 46" LCD panel can be used to create a variety of video wall configurations designed to catch the eye of target consumers. Hisense video wall solutions are a great versatile tool for the delivery of advertisements, product promotions, news updates, or event information.

### Highlights



#### Ultra-narrow bezel

An ultra-narrow 3.5mm bezel-to-bezel width creates a seamless and more perfect picture.



#### Round-the-clock operation

The Hisense L35B5U series can be used as reliable display 24 hours a day, 7 days a week.



#### 178° Wide viewing angle

The extra wide 178° viewing angle is a perfect fit for shoppers, employees or visitors that will view L35B5U displays from diverse angles while passing by.



#### 500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



#### Anti-Glare

Optical technology diffuses mirror-like reflections and bright lights to help keep what's on your screen clear and visible.



#### 1200:1 Ultra high contrast

1200:1 ultra high contrast display, providing eye-catching vivid visuals any time of the day or night, with outstanding colour performance.



## Specifications

### Display

Panel size	46"
Brightness	500nits
Resolution	1920 x 1080
Contrast Ratio	1200:1(typ.)
Back-Light	D-LED
Color	16.7M(8bit)
Viewing Angle	178°/178°
Refresh Ratio	8 ms
Surface Treatment	The surface of the LCD has an Anti-glare coating to minimize reflection and a coating to Reduce scratching. Haze 25%,3H,(Front Polarizer)
Usage time	24x7
MTBF	50,000 hours
Orientation	Landscape & Portrait

### Physical

Splice Pitch	3.5mm
VESA	400x400mm, M6
Set Dimension	1021.98 x 576.57 x 95.5mm 40.24 x 22.7 x 3.76 inch
Packed Dimension	1160 x 240 x 750mm 45.67 x 9.45 x 29.53 inch
Net Weight	20.8 kg / 45.86 lbs
Packed Weight	28.5 kg / 62.84 lbs
20GP container capacity (pcs)	135
40GP container capacity (pcs)	273

### Connectivity

Interface	<ul style="list-style-type: none"> <li>x2 HDMI (in)</li> <li>x2 DP (in &amp; out)</li> <li>x1 DVI (in)</li> <li>x1 VGA (in)</li> <li>x2 RS232 (in &amp; out)</li> </ul>
-----------	---

### Speaker

Built-in Speaker	No
------------------	----

### Power

Voltage	100-240V 50/60Hz
Power Consumption	150W

### Software

OS	Yes
Language	Chinese/English

### Environment

Operation Temperature	10-40°
Operation Humidity	10%-80%RH

### Media Player compatibility

OPS Type Compatible	No
---------------------	----

### Accessories

Basic	Remote Controller, power cord, Ethernet cable, User Manual, RS232 connector, Infrared reception
Optional	Optional Wall Mount, Control Software, Process System

### Certification

Standard Certification CB, CE, ERP **CB CE**

## Display Dimensions

