



100BM66D

100" 4K UHD DIGITAL SIGNAGE DISPLAY

Hisense Digital Signage is designed to serve multiple business applications: public spaces, transportation systems, museums, stadiums, retail stores, hotels, restaurants and corporate buildings. With BM series, it delivers powerful engagement by wireless screen sharing from any devices, boost business with real-time updates, data-driven insights, and visually appealing content, manage and control devices at anytime from anywhere, and simplify the cable management by connecting a series of displays to a single video output.

Highlights



Wireless Screen Sharing

Everything you need for screen sharing solutions. Hisense Share is a in house built-in screen sharing application that enables the screen sharing wirelessly and seamlessly from any devices, anytime, anywhere.



Landscape & portrait

Supports both landscape and portrait orientations. Providing you with endless creative and functional possibilities to fulfil your commercial or informative goals.



Smart Power

A built-in ambient light sensor automatically adjusts the screen brightness according to current light conditions. This display is Energy Star certified to help you protect the environment and save costs.



Content Management System

VisionInfo is a cloud-based digital signage software solution which is flexible, cost-effective, and scalable in its nature. This will give you the freedom to add content as often as you'd like and make sure it looks great across all devices.



Round-the-clock operation

Designed with dual-core System on Chip (SoC) technology, BM series is a reliable digital signage for presenting both offline and cloud based content without disruption or downtime.



4K Ultra HD

Delivers superior resolution that allows more details to be displayed on an image. The materials, the textures, the skin texture and the backgrounds: everything is richer and more realistic.




500 nits

With 500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



Anti-Glare Coating

Offers higher haze value that helps with reflections without notably affecting the image quality.



Specifications

Digital Display Panel

Backlight	DLED
Panel Type	VA
Size	100"
Resolution	3840 x 2160
Refresh rate	120Hz
Color	1.07B
Brightness	500nits
Contrast(typ)	5000:1 (typ)
Response time(typ)	8ms
Viewing angle(Min.)	178°/178°
Color gamut	90% DCI-P3
Haze	25%
Orientation	Landscape & Portrait
Lifetime	50,000 hrs
Operation Hours	7Day x 24Hour

Power

Input	AC 100~240V (50/60Hz)
Power Consumption	500W (Max)
Standby consumption	<0.5W

Physical

Bezel Color	Black
Set Dimension(W×H×D)	2234.6 × 1285.6 × 86.5mm 88 × 50.6 × 3.4inch
Bezel width(T/L/R/B)	13.2mm(T/L/R), 19mm(B)
Net Weight	59.6kg / 131.4lbs
Packing Dimension (W×H×D)	2496 × 1500 × 325mm 98.3 × 59.1 × 12.8inch
Packed Weight	73.5kg / 162.1lbs
VESA	600mm x 600mm

System

OS	Android 9.0
DDR	2G
ROM	16G
Language	English/Chinese/German/French/Polish

Connectivity

Wi-Fi	IEEE 802.11a/b/g/n/ac (2.4G & 5G)
Input	HDMI(2.0) IN x 2 DP(1.2a) IN x1 USB2.0 x 2 RS232 x 1 LAN x 1
Output	HDMI(2.0) OUT x 1 Headphone x 1

Speaker

Built in speaker	15W x 2
------------------	---------

Control Method

Remote	Yes
RS232	Yes

Environment

Temperature	0°~40°C
Humidity	10%~80% RH

What's in the box

Basic	Power cord Remote control RS232 Cable User Manual Battery
-------	---

Certification

Standard Certification	CB/CE/ERP/FCC/CTUVus/CEC/ UKCA/Energy Star	CB CE ERP
------------------------	---	--------------

EAN

Energy Efficiency Class G

Dimensions

100" 2234.6 x 1285.6 x 86.5mm / 88 x 50.6 x 3.4inch
59.6 kg / 131.4lbs

