

GoBoard



65WE3FE

65" ADVANCED INTERACTIVE DISPLAY

Hisense Interactive Display solutions deliver exceptional performance and market leading value. Combining the power of a digital display, tablet, electronic whiteboard and educational tools, Hisense delivers the ultimate all-in-one display solution. Smart OS and ecological abundance, provides best-in-class user experiences while seamless wireless integration makes collaboration both simple and engaging. The NEW GoBoard features the Google Play Store, Android 14.0 operating system and an optimized smart whiteboard to empower your educational activities.

Highlights



Android 14.0 & EDLA certified

Powered by Android 14.0, WE3FE series has greatly enhanced user experience through improvement of hardware compatibility and enrichment and optimization of application ecology. Google Certified can help users to use GMS packages to ensures compatibility and optimal performance with Google applications and services.



Dedicated visual quality for education

High brightness of up to 400 nits and 4K Ultra HD picture quality ensure perfect colour and rich detail. An anti-glare glass panel reduces glare, reflections and fingerprints while maintaining contrast and brightness. And thanks to the 178° viewing angle, every student can perfectly see what appears on the screen.



Smart whiteboard

WE3FE offers an intelligent whiteboard. This whiteboard adopts high-precision infrared touch control, provides a variety of tools including formula editor, mind map, shapes, etc., supports four-split screen display, and handwriting can be easily converted to standard font. By integrating the above functions into the whiteboard, teaching and learning will be simplified.



Caring for the eyes

Certified by TÜV Rheinland, the WE3FE series effectively reduces harmful blue light and ensures a more comfortable viewing experience, reducing the risk of eye fatigue and headaches with prolonged use.





Pluggable WiFi Module

With a pluggable WiFi module, information security is protected from leakage, and you can make a quick replacement of the WiFi module on failure. Other than that, the pluggable module is more stable than the fixed ones due to its independent circuit design and heat dissipation structure.



A better writing experience

With up to 40 touch points, the WE3FE allows multiple users to annotate simultaneously, increasing engagement and encouraging group collaboration. The panel features an impressively low writing height, provides a smooth and natural writing experience that feels like writing on paper, effectively reducing latency and allowing for a smoother operating experience.




Quick & easy screen sharing

WE3FE supports webcast, airplay, Miracast, Chromecast, etc. Dual WiFi modules simultaneously support a screen sharing hotspot and a WiFi network connection. With low image latency, you'll enjoy a faster, more stable connection and a superior screen sharing experience.



Energy Star Certified

The WE3FE is Energy Star 8.0 certified and significantly reduces power consumption and the impact on the environment compared to similar products on the market.





Specifications

Interactive Display Panel	
LCD Size	65"
Backlight Type	D-LED
Resolution	3840x2160(pixels)
Brightness	400nits(typ.)
Contrast Ratio	5000:1(typ.)
Response Time	6.5ms(typ.)
Refreshing Frequency	60Hz
Viewing Angle	178°(H) / 178°(V)
Lifetime(typ.)	30,000 hrs(min.)
Color Gamut(X% NTSC)	72%(typ.)
Display Colors	1.07B(10bit)
System	
СРИ	Architecture - Core Cortex-A73x4 Working Frequency - 1.39GHz(max.)
GPU	MaliG52 MC1
RAM	8GB
ROM	128GB
OS	Android 14.0
	English (default), Chinese, French, Spanish, German, Italian, Polish, Finnish, Norwegian, Swedish, Thai, Indonesian, Japanese, Russian,
Language	Arabic, Vietnamese, Serbian, Kazakh; Croatian, Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay
Power	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish,
	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish,
Power	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay
Power Requirements	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max)
Power Requirements Power Consumption Without OPS	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.)
Power Power Requirements Power Consumption Without OPS Standby Consumption	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.)
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in)	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power Physical	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W DC 18V/3.5A
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power Physical Product Size (W x H x D)	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W DC 18V/3.5A 1491 x 898.5 x 98.8mm 58.7 x 35.4 x 3.9 inch 1628 x 1014 x 185mm
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power Physical Product Size (W x H x D) Package Size (W x H x D)	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W DC 18V/3.5A 1491 x 898.5 x 98.8mm 58.7 x 35.4 x 3.9 inch 1628 x 1014 x 185mm 64.1 x 40 x 7.3 inch
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power Physical Product Size (W x H x D) Package Size (W x H x D) Net Weight	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W DC 18V/3.5A 1491 x 898.5 x 98.8mm 58.7 x 35.4 x 3.9 inch 1628 x 1014 x 185mm 64.1 x 40 x 7.3 inch 36.15kg / 79lbs
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power Physical Product Size (W x H x D) Package Size (W x H x D) Net Weight Packed Weight	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W DC 18V/3.5A 1491 x 898.5 x 98.8mm 58.7 x 35.4 x 3.9 inch 1628 x 1014 x 185mm 64.1 x 40 x 7.3 inch 36.15kg / 79lbs 41.7kg / 91lbs
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power Physical Product Size (W x H x D) Package Size (W x H x D) Net Weight Packed Weight 20GP Container Capacity (pcs)	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W DC 18V/3.5A 1491 x 898.5 x 98.8mm 58.7 x 35.4 x 3.9 inch 1628 x 1014 x 185mm 64.1 x 40 x 7.3 inch 36.15kg / 79lbs 41.7kg / 91lbs 72
Power Power Requirements Power Consumption Without OPS Standby Consumption Speaker (Built-in) OPS Power Physical Product Size (W x H x D) Package Size (W x H x D) Net Weight Packed Weight 20GP Container Capacity (pcs)	Slovenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay AC 100 V ~ 240 V, 50/60 Hz 335W (Max) 180W (typ.) <0.5W 2x16W DC 18V/3.5A 1491 x 898.5 x 98.8mm 58.7 x 35.4 x 3.9 inch 1628 x 1014 x 185mm 64.1 x 40 x 7.3 inch 36.15kg / 79lbs 41.7kg / 91lbs 72

I	0	L	IC	. [1	

Sensing Type	Infrared Touch Frame
Surface Protection	Anti-Glare Glass
Infrared Touch	OPS: ≤40 points Android: ≤32 points (EDLA)
Touch Accuracy	90%(±1mm)
Theory Clicks	Unlimited
Minimum Touch Object	3mm
Writing Height	1.5mm
Windows 11/10/8/7,Android	Multi Touch

Connectivity

Wi-Fi	IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G)
Bluetooth	BT5.2
NFC	w/o
Camera	w/o
Input	HDMI(2.0) IN x3 DP(1.2a) IN x1 VGA IN x1 OPS(optional) x1 LAN IN x1 (1000 baseT) USB2.0 x2 USB3.0 x3 Type-C x2 (frontx 1: support PD 65W) Touch x3 Audio IN x1 RS232 IN x1 (RJ45) TF Card x1
Output	HDMI OUT x1 S/PDIF OUT x1

Environment

Output

Operation Temperature	0-40°C
Operation Humidity	20% - 80%RH

Audio OUT x1 LAN OUT x1 (1000 baseT)

Accessories

Basic	User Manual x1 Pen x2 Remote Control x1 Power Cable x1 (Country Dependent) Battery x2 Wall Mount Bracket x1
Optional	Mobile Cart OPS

Certification

CB/CE/ERP/SouthAfrica Energy Efficiency/cTUVus/ CEC/UKCA/FCC/IC/RCM/Energy Star/EDLA **Standard Certification**





Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.





Dimensions

65" 1491 x 898.5 x 98.8mm / 58.7 x 35.4 x 3.9inch 36.15kg / 79lbs

