

HTJ series

Indoor LED Display

Model: HTJ1.2



Specifications

Pixel Pitch (mm)	P1.25
LED package	Filp-chip COB (1 red,1 green,1 blue)
Thickness(mm)(Excluding protrusions part)	31mm
Thickness(inch)	1.22
Module Resolution	120*135
Module Size (W×H/mm)	150*168.75
Module Size (W×H/inch)	5.91*6.64
Cabinet Dimension (W×H/mm)	600*337.5
Cabinet Dimension(W×H/inch)	23.62*13.29
Cabinet Resolution	480*270
Cabinet Weight (kg/panel)	≤4.1kg
Cabinet Weight (lbs/panel)	≤9.04lbs
Cabinet materials	Die-cast aluminum
Gray Level	14 bit
Color Gamut	>113% DCI-P3
Brightness (max./peak.)	1,000nits / 1,600nits
Contrast Ratio (typ./peak.)	25,000 : 1 @10lux 40,000 : 1 @10lux
Connectivity	HDMI 2.0 (up 4K@60Hz)
Maintenance	Front Access
Max Power Consumption (W/sqm)	≤288@1,000nits
Avg Power Consumption (W/sqm)	≤98
Viewing Angle (H/V)°	165/150
Brightness Uniformity	98%
Color Uniformity	± 0.003 Cx,Cy
Color Temperature	6500K
Refresh Rate (Hz)	3,840 Hz (typ.)
Operating Environment	From 0~40°C
Relative Humidity	10~70%RH
Lifetime(typ)	100,000 Hrs

* Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

Display Dimensions

