Hisense

GoBoard Live Pro

Native Apps





















65WM6FE

65" ADVANCED INTERACTIVE DISPLAY

Hisense Interactive Display solutions deliver exceptional performance and market leading value. Integrating the power of an interactive display, smart whiteboard, powerful microphone array and stereo speaker, Hisense delivers the ultimate all-in-one display solution. Smart OS and ecological abundance, provides best-in-class user experiences while seamless wireless integration makes collaboration both simple and engaging. The NEW GoBoard Live Pro display features Google Play Store, Android 13.0 operating system and optimized smart white board to empower your business.

Highlights



Anti-glare 9H Scratch-resistant Glass

Featuring anti-glare glass, this display reduces light reflection and maintains screen clarity in strong light. With 9H scratch resistance, it withstands daily wear and provides smooth touch operation and clear visuals



Android 13 & EDLA certified

Powered by Octa-core Processor and Android 13 OS, the GoBoard Live Pro enhances system efficiency, stability, and compatibility. With EDLA certified, it ensures synchronization for built-in Google apps and accounts, providing access to Google Play Store, security updates, and certified Android applications.



Integrated 4K camera

The GoBoard Live Pro features an integrated 4K camera designed with a physical cover and a working light, delivering enhanced visual clarity while safeguarding participant confidentiality. The 4K UHD display effectively presents captured images with vibrant, lifelike colors, ensuring sharp and crisp details.



Smart Whiteboard

The GoBoard Live Pro adopts high-level touch up to 55 points and ultra-low writing height of ≤1.5mm allowing you to naturally and accurately capture ideas with near-zero latency. You can experience quarto sense,smart graphics,smart tables and handwriting can be easily converted to standard font.



Caring for the eyes

Certified by TÜV Rheinland, the GoBoard Live Pro can effectively reduce the harmful blue light and guarantees a more comfortable viewing experience, with a reduced risk of tired eyes and headaches with a prolonged use.



Dolby Atmos

As the only interactive board equipped with Dolby Atmos, let alone a speaker power of 61W, the Hisense GoBoard Live Pro stands out with an unprecedented immersive sound experience, no matter where you are in the conference room or classroom, you can enjoy true-to-life sound effects.



Energy Star Certified


The GoBoard Live Pro is certified with Energy Star 8.0, achieving exceptional energy efficiency and minimizing operational costs. This certification ensures adherence to strict environmental standards, extends device lifespan through optimized thermal management, and promotes sustainability goals.



Quick & easy screen sharing

The GoBoard Live Pro supports 5 types of screen sharing, allowing up to 9 devices to share simultaneously. It features effective control to prevent malicious casting and supports continuous 8-hour screen casting without disconnecting.







Specifications

Interactive Display Panel	
LCD Size	65"
Backlight Type	D-LED
Resolution	3840x2160(pixels)
Brightness	400nits(typ.)
Contrast Ratio	1200:1(typ.)
Response Time	8ms (typ.)
Refreshing Frequency	60Hz
Viewing Angle	178°(H) / 178°(V)
Lifetime	50,000 hrs (min.)
Color Gamut(X% NTSC)	72%
Display Colors	1.07B(10bit)
System	
СРИ	Architecture - A73x4 + A53x4 Octa-core Working Frequency - 2.2GHz + 2.0GHz
GPU	MaliG52
RAM	8GB
ROM	128GB
Operating System	Android 13.0
Language	English (default), Chinese, French, Spanish, German, Italian, Polish, Finnish, Norwegian, Swedish, Thai, Indonesian, Japanese, Ruscian, Arabic, Viethanmese, Serbian, Kazakh; Croatian, Slowenian, Czech, Slovak, Hungarian, Romanian, Bugarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay
Power	
Power Requirements	AC 100 V ~ 240 V, 50/60 Hz
Power Consumption without OPS	240W (Max) / 159.5W (Typ.)
Standby Consumption	<0.5W
Built In Speaker	2x18W+25W
Connectivity	
, , , , , , , , , , , , , , , , , , ,	DC 18V/5A
Connectivity OPS Power Wi-Fi	DC 18V/5A IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G)
OPS Power	IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G)
OPS Power Wi-Fi	IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G)
OPS Power Wi-Fi Bluetooth	IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G) BT5.3
OPS Power Wi-Fi Bluetooth	IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G) BT5.3

Sensing Type	Infrared Touch Frame
Surface Protection	Anti-Glare Glass
Infrared Touch	≤55 points (OPS) ≤55 points (Android) ≤40 points (MAC)
Touch Accuracy	90%(±1mm)
Theory Clicks	Unlimited
Minimum Touch Object	2mm
Writing Height	≤1.5mm (Support Quatro Sense)
Windows 11/10/8/7,Android	Multi Touch
Physical	
Product Size (W x H x D)	1488.1 x 935.1 x 121.7mm 58.6 x 36.8 x 4.8 inch
Package Size (W x H x D)	1629 x 1040 X 240mm 64.1 x 40.9 x 9.4inch
Net Weight	35.0kg / 77.2lbs
Packed Weight	45.0kg / 99.2lbs
Housing Material	Front Shell: Aluminium Rear Shell: Plastic
Housing Colour	Black + Tarnish
VESA	600 x 400mm, 4-M8 Screw
Environment	
Operation Temperature	0 - 40°
Operation Humidity	20% - 80%
Certification	
Standard Certification Accessories	CB/CE/ERP/SouthAfrica Energy Efficiency/cTUV CEC/UKCA/FCC/IC/RCM/Energy Star/EDLA
Basic	User Manual×1 Pen×2 Remote Control×1 Power Cable×1 (Country Dependent) Battery×2 Wall Mount Bracket×1
Optional	Mobile Cart Wireless Casting Dongle OPS





Dimensions

