# Hisense

# **GoBoard** Live Pro

#### Native Apps





















## **75WM6FE**

## 75" ADVANCED INTERACTIVE DISPLAY

Hisense Interactive Display solutions deliver exceptional performance and market leading value. Integrating the power of an interactive display, smart whiteboard, powerful microphone array and stereo speaker, Hisense delivers the ultimate all-in-one display solution. Smart OS and ecological abundance, provides best-in-class user experiences while seamless wireless integration makes collaboration both simple and engaging. The NEW GoBoard Live Pro display features Google Play Store, Android 13.0 operating system and optimized smart white board to empower your business.

### Highlights



#### Anti-glare 9H Scratch-resistant Glass

Featuring anti-glare glass, this display reduces light reflection and maintains screen clarity in strong light. With 9H scratch resistance, it withstands daily wear and provides smooth touch operation and clear visuals



#### Android 13 & EDLA certified

Powered by Octa-core Processor and Android 13 OS, the GoBoard Live Pro enhances system efficiency, stability, and compatibility. With EDLA certified, it ensures synchronization for built-in Google apps and accounts, providing access to Google Play Store, security updates, and certified Android applications.



#### Integrated 4K camera

The GoBoard Live Pro features an integrated 4K camera designed with a physical cover and a working light, delivering enhanced visual clarity while safeguarding participant confidentiality. The 4K UHD display effectively presents captured images with vibrant, lifelike colors, ensuring sharp and crisp details.



#### **Smart Whiteboard**

The GoBoard Live Pro adopts high-level touch up to 55 points and ultra-low writing height of ≤1.5mm allowing you to naturally and accurately capture ideas with near-zero latency. You can experience quarto sense, smart graphics, smart tables and handwriting can be easily converted to standard font.



#### Caring for the eyes

Certified by TÜV Rheinland, the GoBoard Live Pro can effectively reduce the harmful blue light and guarantees a more comfortable viewing experience, with a reduced risk of tired eyes and headaches with a prolonged use.



#### **Dolby Atmos**

As the only interactive board equipped with Dolby Atmos, let alone a speaker power of 61W, the Hisense GoBoard Live Pro stands out with an unprecedented immersive sound experience, no matter where you are in the conference room or classroom, you can enjoy true-to-life sound effects.



#### **Energy Star Certified**


The GoBoard Live Pro is certified with Energy Star 8.0, achieving exceptional energy efficiency and minimizing operational costs. This certification ensures adherence to strict environmental standards, extends device lifespan through optimized thermal management, and promotes sustainability goals.



#### Quick & easy screen sharing

The GoBoard Live Pro supports 5 types of screen sharing, allowing up to 9 devices to share simultaneously. It features effective control to prevent malicious casting and supports continuous 8-hour screen casting without disconnecting.







# Specifications

Interactive Display Panel		Touch	
LCD Size	75"	Sensing Type	Infrared Touch Frame
Backlight Type	D-LED	Surface Protection	Anti-Glare Glass
Resolution	3840x2160(pixels)		≤55 points (OPS)
Brightness	400nits(typ.)	Infrared Touch	≤55 points (Android)
ontrast Ratio	1200:1(typ.)		≤55 points (MAC)
Response Time	8ms (typ.)	<b>Touch Accuracy</b>	90%(±1mm)
efreshing Frequency	60Hz	Theory Clicks	Unlimited
liewing Angle	178°(H) / 178°(V)	Minimum Touch Object	2mm
ifetime	50,000 hrs (min.)	Writing Height	≤1.5mm (Support Qu
Color Gamut(X% NTSC)	72%	Windows 11/10/8/7,Android	Multi Touch
Display Colors	1.07B(10bit)	Physical	
System		Product Size (W x H x D)	1709.9 x 1060.1 x 12
рU	Architecture - A73x4 + A53x4 Octa-core Working Frequency - 2.2GHz + 2.0GHz		67.3 x 41.7 x 5.0 inch 1850 x 1165 x 240mi
Ρ	MaliG52	Package Size (W x H x D)	72.8 x 45.9 x 9.4 inch
		Net Weight	45.8kg / 101.0lbs
AM	8GB	Packed Weight	60.0kg / 132.3lbs
OM perating System	128GB Android 13.0	Housing Material	Front Shell: Aluminiur Rear Shell: Plastic
peraturg system	English (default), Chinese, French, Spanish, German, Italian,	Housing Colour	Black + Tarnish
inguage	Polish, Finnish, Norwegian, Swedish, Thai, Indonesian, Japanese, Russian, Arabic, Viethamese, Serbian, Kazakh; Croatian, Slowenian, Czech, Slovak, Hungarian, Romanian, Bulgarian, Albanian, Macedonian, Greek, Turkish, Afrikaans, Malay	vesa Environment	600 x 600mm, 4-M8
Power		Operation Temperature	0 - 40°
		Operation Humidity	20% - 80%
ower Requirements	AC 100 V ~ 240 V, 50/60 Hz	Operation numbers	20% - 60%
ower Consumption without OPS	350W (Max) / 213.2W (Typ.)	Certification	
tandby Consumption	<0.5W		
uilt In Speaker	2x18W+25W	Standard Certification	CB/CE/ERP/SouthAfrica En CEC/UKCA/FCC/IC/RCM/En
Connectivity		Accessories	
PS Power	DC 18V/5A		
/i-Fi	IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G)	Basic	User Manual×1 Pen×2 Remote Control×1
luetooth	BT5.3	Dasic	Power Cable×1 (Cour Battery×2
IFC	Yes		Wall Mount Bracket×
Camera	Yes		Mobile Cart
nput	HDMI (2.1) IN x3 with 4K Support OPS (Optional) x1 LAN x1 (1000baseT R) USB2.0 x1 USB3.0 x3 Type-C x1 (Support PD 65W) Touch x1 Audio In x1 RS-232 In x1(RJ45)	Optional	Wireless Casting Dor OPS
Output	RS232 OUT x1 (RJ45) HDMI Out x1 COAX Out x1 Audio Out x1		





Audio Out x1



## **Dimensions**



