Hisense



86GM50D 86" 4K UHD DIGITAL SIGNAGE DISPLAY

Hisense Digital Signage is designed to serve multiple business applications: public spaces, transportation systems, museums, stadiums, retail stores, hotels, restaurants and corporate buildings. With GM50D series, it delivers powerful engagement from any devices, boost business with real-time updates, data-driven insights and visually appealing content, manage and control devices at anytime from anywhere, and simplify the cable management by conecting a series of displays to a single video output.

Highlights



Narrow Bezel

With a narrow bezel and symmetrical design, the display can be easily integrated into any environment. All terminals face outwards, ensuring the display hangs flush against the wall which saves space and facilitates installation.



Clean Cable Solution

The integrated cable holder hides cables and keeps the back of the display tidy and uncluttered. This reduces visual distractions that can get in the way of your viewing experience.



Wireless Screen Sharing

Everthing you need for screen sharing solutions. ScreenShare is a in house built-in screen sharing application that enables the screen sharing wirelessly and seemlessly from anywhere and from any devices.



Mobile Device Management

VisionInfo is a cloud-based device managemet software that offers end-to-end device management and control through all devices. It is a powerful, effective and easy to use tool to control your devices at anytime from anywhere.









Android 11

Android 11 works to keep your data safe and secure. With Android 11, you have more control over what information apps can and can't access. Devices that work better together, enhance your messaging, audio and multitasking experiences.



Anti-glare Coating

All GM50D Series displays offer higher haze panels that help reduce reflections without adversley affecting the image quality. Anti-glare coatings can also improve the perceived contrast of the display.

Smart Power

The backlight intensity can be controlled and pre-set by the system to reduce the power consumption, ENERGY STAR-certified, the display helps you protect the environment and save costs.



Conformal Coating

Electronic components are completely protected from the environmental factors like moisture, dust, salt, chemicals, temperature changes and mechanical abrasion.

Hisense

Specifications

Digital Display Panel

Backlight Type	DLED
Туре	ADS
Size	86"
Resolution	3840 x 2160
Refresh rate	60Hz
Color Depth	1.07G (8 Bits+FRC)
Brightness(Typ.)	500 nits
Contrast Ratio(Typ.)	1200:1
Response Time(Typ.)	8ms
Viewing Angle(Min.)	178°/178°
Color Gamut(Typ.)	72% NTSC
Haze	25%
Orientation	Landscape & Portrait
Lifetime	up to 50,000 hrs
Operation Hours	7Day x 18Hour

System

Operating System	Android 11		
Processor CPU	ARM Cortex-A55 Quad core		
Processor GPU	Mali-G52		
Memory	3G DDR4		
Storage	32G EMMC		
Language	Simplified Chinese, English, French, German, Polish, Spanish, Russian, Italian, Finnish, Norwegian, Swedish, Hebrew, Arabic, Thai, Malay, Indonesian		

Connectivity

WI-FI Bluetooth	2.4/5.0GHz dual,802.11a/b/g/n/ac BT5.1
Input	HDMI(2.0) x 2 DP(1.2a) x 1 USB2.0(A) x 1 USB3.0(A) x 1 USB3.0(A) x 1 RS232(RJ45) x 1 LAN(RJ45) x 1
Output	HDMI x 1 Audio(3.5mm) x 1 RS232(RJ45) x 1

Physical

Bezel Color	Black
Set Dimension(W×H×D)	1926.6 x 1095.5 x 64.2mm 75.9 x 43.1 x 2.5inch
Bezel width(T/L/R/B)	10.3mm(T/L/R), 10.8mm(B)
Net Weight	38.2kg / 84.2lbs
Packing Dimension (W×H×D)	2117 x 1298 x 269mm 83.3 x 51.1 x 10.6inch
Gross Weight	59.5kg / 131.2lbs
VESA Mount	600mm x 400mm

Power Power Supply AC 100~240V (50/60Hz) Power Consumption (Typ.) 200W Power Consumption (Max.) 325W Standby Consumption <0.5W (Standby Mode) Speaker Built in speaker 10W x 2 Environment 0°~40°C **Operating Temperature Operating Humidity** 10%~80% Non-Condensing What's in the box Quick Setup Guide Warranty Card Power Cord Standard Remote Controller Battery (AAA) x 2

Certification

Standard Certification	CCC/CB/CE/FCC/cTUVus/UKCA/CEC/ERP	
Safety	62368-1	
Enviroment	Energy Star 8.0	energy
IP Rating	IP5X	ENERGY STAR

RS232 Converter Cable

Dimensions

38.2kg / 84.2lbs

86" 1926.6 x 1095.5 x 64.2mm / 75.9 x 43.1 x 2.5inch 38.2kg / 8/, 7lbc



Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

Learn More: www.hisense-b2b.com | Contact Us: sales@hisense-b2b.com

Hisense commercial DISPLAY

📊 @Hisense B2B Europe | @Hisense B2B USA | @Hisense B2B MENA | @Hisense B2B Indonesia | @Hisense B2B South Africa | @Hisense B2B Australia